

2-Track Out

Type	RCA connector
Impedance	1 k Ω
Max. output level	+22 dBu

DSP

Type	KLARK TEKNIK
Converter	24-bit Sigma-Delta
	64/128-times oversampling
Sampling rate	40 kHz

Wireless Input

USB dongle	Accepts signals from 2 independent Behringer ULM mics
------------	---

Main Mix System Data (Noise)

Main mix @ $-\infty$, channel fader @ $-\infty$	-100 dB / -103 dB A-weighted
Main mix @ 0 dB, channel fader @ $-\infty$	-88 dB / -91 dB A-weighted
Main mix @ 0 dB, channel fader @ 0 dB	-80 dB / -82 dB A-weighted

Power Supply

Mains voltage	100 – 240 V~, 50/60 Hz
Power consumption	50 W
Fuse (100 - 240 V~, 50/60 Hz)	T 1.6 A H 250 V
Mains connector	Standard IEC receptacle

USB

Connector	Type B
Audio	Stereo in/out
Converter	16-bit
Sample rate	48 kHz

Physical/Weight

Dimensions (W x D x H)	430 x 370 x 90 mm (16.9 x 14.6 x 3.5")
Weight	4.7 kg (10.4 lbs)

QX1622USB**Microphone Inputs**

XENYX Mic preamps	4
Type	XLR connector, balanced, discrete input circuit

Mic E.I.N. (20 Hz - 20 kHz)

@ 0 Ω source resistance	-134 dB / -136 dB A-weighted
@ 50 Ω source resistance	-131 dB / -133 dB A-weighted
@ 150 Ω source resistance	-129 dB / -131 dB A-weighted
Frequency response	<10 Hz - 150 kHz (-1 dB) <10 Hz - 200 kHz (-3 dB)
Gain range	+10 dB to +60 dB
Max. input level	+12 dBu @ +10 dB gain
Impedance	2 k Ω balanced
Signal-to-noise ratio	107 dB / 110 dB A-weighted (0 dBu In @ +22 dB gain)
Distortion (THD+N)	0.005% / 0.004% A-weighted
Phantom power	Switchable, +48 V

Line Input

Type	¼" TRS connector, balanced
Impedance	20 k Ω balanced, 10 k Ω unbalanced
Gain range	-10 dB to +40 dB
Max. input level	30 dBu

Frequency Response (Mic In \rightarrow Main Out)

<10 Hz - 160 kHz	± 3 dB
------------------	------------

Stereo Inputs

Type	4 x ¼" TRS connector, balanced
Impedance	20 k Ω balanced, 10 k Ω unbalanced
Gain range	-20 dB to +20 dB
Max. input level	+22 dBu

2-Track In

Type	RCA connector
Impedance	10 k Ω
Max. input level	+22 dBu

Equalizer 3-Band Semi-Parametric

Low	80 Hz / ± 15 dB
Mid	Variable 100 Hz - 8 kHz / ± 15 dB
High	12 kHz / ± 15 dB

Equalizer 4-Band Fixed

Low	80 Hz / ± 15 dB
Low mid	500 Hz / ± 15 dB
High mid	3 kHz / ± 15 dB
High	12 kHz / ± 15 dB

Channel Inserts

Type	$\frac{1}{4}$ " TRS connector, unbalanced
Max. input level	+22 dBu

AUX Sends

Type	2 x $\frac{1}{4}$ " TRS connector, balanced
Impedance	120 Ω
Max. output level	+22 dBu

AUX Returns

Type	2 x $\frac{1}{4}$ " TRS connector, balanced
Impedance	20 k Ω balanced, 10 k Ω unbalanced
Max. input level	+22 dBu

Main Outputs

Type	XLR and $\frac{1}{4}$ " connectors, balanced
Impedance	240 Ω balanced, 120 Ω unbalanced
Max. output level	+28 dBu

Control Room Output

Type	$\frac{1}{4}$ " TRS connector, balanced
Impedance	120 Ω
Max. output level	+22 dBu

Phones Output

Type	$\frac{1}{4}$ " TRS connector, unbalanced
Impedance	25 Ω
Max. output level	+21 dBu / 150 Ω (+25 dBm)

2-Track Out

Type	RCA connector
Impedance	1 k Ω
Max. output level	+22 dBu

DSP

Type	KLARK TEKNIK
Converter	24-bit Sigma-Delta
	64/128-times oversampling
Sampling rate	40 kHz

Wireless Input

USB dongle	Accepts signals from 2 independent Behringer ULM mics
------------	---

Main Mix System Data (Noise)

Main mix @ $-\infty$, channel fader @ $-\infty$	-100 dB / -102 dB A-weighted
Main mix @ 0 dB, channel fader @ $-\infty$	-88 dB / -91 dB A-weighted
Main mix @ 0 dB, channel fader @ 0 dB	-82 dB / -85 dB A-weighted

Power Supply

Mains voltage	100 – 240 V~, 50/60 Hz
Power consumption	50 W
Fuse (100 - 240 V~, 50/60 Hz)	T 1.6 A H 250 V
Mains connector	Standard IEC receptacle

USB

Connector	Type B
Audio	Stereo in/out
Converter	16-bit
Sample rate	48 kHz

Physical/Weight

Dimensions (W x D x H)	325 x 348 x 90 mm (12.8 x 13.7 x 3.5")
Weight	3.5 kg (7.7 lbs)

Asio is a trademark or registered trademark of Steinberg Media Technologies GmbH.