



See nothing, hear everything

The CCM664SR is a dual, two-way ceiling speaker featuring a 150mm(6in) woven glass fibre cone bass/midrange driver and two offset soft dome tweeters. The twin voice coil bass/midrange driver and tweeters allow a stereo signal to be combined to facilitate the use of just one ceiling speaker in a single installation area without the loss of one audio channel. The CCM664SR also includes a two-position stereo/surround switch to instantly make the speaker very suitable to be used as a surround channel. Incorporating QuickDogs™ and plug-and-play functionality it is quick and easy to install.

Technical Specifications

Description	2-way dual channel in-ceiling system
Drive Units	2x ø20mm (1in) soft dome tweeter 1x ø150mm (6in) black glassfibre cone bass/midrange
Frequency Range (-6dB)	48Hz – 30kHz
Recommended Amp Power	25 – 80w (per channel)
Sensitivity SPL (2.83V, 1m)	82dB (per channel) 88dB (both channels driven)
Impedance Nominal (min)	8Ω (4Ω) (per channel)
Frame diameter	240mm (9.5in)
Cut-out diameter	202mm (8in)
Depth behind surface	133mm (5.2in)
Protrusion	4mm (0.2in)
Pre-mount Kit	PMK C6
Back Box	BB C6

