

QuickSmart Mobile application. High-resolution, low-latency Bluetooth\* streaming ensures excellent results for music playback or accompaniment.

**SINGLE-TRIP PORTABILITY** 



EVOLVE 30M
PORTABLE COLUMN SYSTEM



# EVOLVE 30M

## REFINED INDUSTRIAL DESIGN AND PROFESSIONAL-GRADE **EV-ENGINEERED COMPONENTS**

The EVOLVE 30M sounds as good as it looks. The full-range column array and its six lightweight 2.8" neodymium drivers provide ultra-wide 120° coverage via proprietary waveguides; array-formed 40° asymmetrical vertical coverage ensures acoustic output is directed towards both sitting and standing audience members. A 10" subwoofer is housed in a 15 mm wood enclosure for enhanced rigidity and acoustical performance. A Class-D amplifier provides up to 1000 W of output power. The array and sub are connected via a two-piece symmetrical aluminum pole with internal wiring and magnetically assisted latching.

## INDUSTRY-LEADING OUICKSMART DSP

QuickSmart DSP allows navigation of system parameters via an LCD with single-knob control or via the app, as well as multiple options for signal routing and inputs. Functions include four presets (Music, Live, Speech, Club), three-band system EQ (low, mid, high), seven-band graphic EQ (in Mixer mode), five user-programmable presets (Store and Recall settings), phantom power, visual monitoring of limiter status, input level control and meters, and a master volume control to optimize gain structure.

## ONBOARD MIXER GIVES YOU BEST-IN-CLASS **CONNECTIVITY AND CONTROL**

Developed in collaboration with the world-class audio electronics engineering team at EV's sibling brand Dynacord, the integrated fully featured, fully configurable digital mixer has multiple inputs with professional-grade preamps and mix functions. The mixer can be controlled via the QuickSmart Mobile app or via the LCD/single-knob interface.

## FINESSE YOUR SOUND WITH MUSICIAN-FRIENDLY FEATURES

Independent channel aux sends and Hi-Z and foot switch inputs are included for flexible system configuration, and a range of onboard studio-quality effects (30 presets, including chorus, delay, flange and reverb, via two FX channels) add myriad options for musicians to fine-tune their tone - and reduce the amount of gear they need to bring to the gig. The onboard effects can be controlled via the QuickSmart Mobile app or via the LCD/singleknob interface.

The EVOLVE 30M joins the larger EVOLVE 50 in the awardwinning Electro-Voice EVOLVE column speaker system series.

## TECHNICAL SPECIFICATIONS

Frequency response (-3 dB)1: 51 Hz - 20 KHz Frequency range (-10 dB)<sup>1</sup>: 45 Hz - 20 KHz Maximum SPL<sup>2</sup>: 123 dB Coverage (H x V): 120° x 40° Amplifier rating: 1000 W LF channel rating: 500 W HF channel rating: 500 W Crossover frequency: 200 Hz

> Connectors: 4x XLR/TRS combo jack line/mic input

2x XLR/TRS combo jack for stereo line input

1x 1/4" TRS Hi-Z input 1x stereo RCA input 1x 3.5 mm stereo input

1x wireless stereo Bluetooth® audio input

1x 1/4" foot switch input 1x XI R mix out output 1x XLR aux out output

Enclosure: Column: composite

Pole (2 pcs): aluminum Sub: 15 mm plywood

Grille: Steel with black or white powder coat

Color: Black or white

**Dimensions (HxWxD): mm (in)** Column: 620 x 95 x 157 (24.4 x 3.7 x 6.2)

Pole (2 pcs): 600 x 48 x 55 (23.6 x 1.9 x 2.2) Sub: 448 x 332 x 432 (17.6 x 13.1 x 17)

Net weight: Column: 6.0 lb (2.7 kg)

Pole (2 pcs): 3.1 lb (1.4 kg) Sub: 34.9 lb (15.8 kg)

Bag for column and pole: 1.9 lb (0.85 kg)

Power consumption<sup>3</sup>: 100-240 V AC, 50-60 Hz, 1.5-0.6 A











www.electrovoice.com/evolve30m

<sup>&</sup>lt;sup>1</sup>Hall<sup>-</sup>space measurement using live DSP preset. <sup>2</sup>Maximum SPL is measured at 1 m using broadband pink noise at maximum output. <sup>3</sup>Current rating is 1/8 power.