


electrovoice.com/livex

POWERED













12" TWO-WAY POWERED LOUDSPEAKER

37.04 LB | 16.8 KG

A compact, powerful and versatile choice for sound reinforcement and stage monitoring applications—lightweight and durable, with a 1000 W amplifier.

- 12" woofer and 1.5" high-frequency titanium compression driver
- 50 Hz 20 kHz frequency range; 132 dB max SPL
- Lightweight 1000 W Class-D amplifier—runs cool without fans
- Easy to connect and control with versatile input and output options
- Rugged wood cabinet—pole-mounts or stacks with Live X subwoofers

49.6 LB | 22.5 KG

15" TWO-WAY POWERED LOUDSPEAKER

A powerful step up from the ELX112P, the 15" woofer and 1000 W amplifier in the ELX115P deliver extended lower frequencies and room-filling volume.

- 15" woofer and 1.5" high-frequency titanium compression driver
- 44 Hz 20 kHz frequency range; 134 dB max SPL
- Lightweight 1000 W Class-D amplifier—runs cool without fans
- Easy to connect and control with versatile input and output options
- Rugged wood cabinet—pole-mounts or stacks with Live X subwoofers

18

ELX118P










18" POWERED SUBWOOFER

69 LB | 31.3 KG

Optimized for performance with the ELX112P and ELX115P, the ELX118P adds a full, deep, low-frequency, amplified punch that you can hear and feel.

- 18" woofer for powerful, engaging bass response
- 32 Hz 130 Hz frequency range; 134 dB max SPL
- 700 W Class-D amplifier—runs cool without fans
- Rugged wood cabinet—supports pole-mounted or stacked configurations







18" PASSIVE SUBWOOFER

67.46 LB | 30.6 KG

Optimized for performance with the ELX112 and ELX115, the ELX118 adds a full, deep, low-frequency punch that you can hear and feel.

- 18" woofer provides extended low-frequency output
- 35 Hz 200 Hz frequency range
- 96 dB SPL sensitivity; 134 dB max SPL
- 400 W continuous and 1600 W peak power handling
- Rugged wood cabinet—supports pole-mounted or stacked configurations



89.73 LB | 40.7 KG

DUAL 15" TWO-WAY PASSIVE LOUDSPEAKER

This dual-woofer configuration delivers real low end punch—ideal for applications that demand high volume output and an ultra-wide frequency response from a single cabinet.

- Dual 15" woofers and 1.5" high-frequency titanium compression driver
- 38 Hz 20 kHz frequency range
- 96 dB SPL sensitivity; 137 dB max SPL
- 600 W continuous and 2400 W peak power handling
- Rugged wood cabinet creates serious stage presence







12" TWO-WAY PASSIVE LOUDSPEAKER

35.27 LB | 16 KG

The versatile ELX112 loudspeaker is a compact, powerful choice with real stage presence, for sound reinforcement and stage monitoring applications.

- 12" woofer and 1.5" high-frequency titanium compression driver
- 55 Hz 20 kHz frequency range
- 94 dB SPL sensitivity; 132 dB max SPL
- 250 W continuous and 1000 W peak power handling
- Rugged wood cabinet—pole-mounts or stacks with Live X subwoofers

48.28 LB | 21.9 KG

15" TWO-WAY PASSIVE LOUDSPEAKER

A powerful step up from the ELX112, the ELX115 features a 15" woofer that delivers extended low-frequency response for bigger sound in larger rooms.

- 15" woofer and 1.5" high-frequency titanium compression driver
- 50 Hz 20 kHz frequency range
- 95 dB SPL sensitivity; 134 dB max SPL
- 400 W continuous and 1600 W peak power handling
- Rugged wood cabinet—pole-mounts or stacks with Live X subwoofers


PASSIVE

Live X PASSIVE LOUDSPEAKERS



The Live X series includes four versatile solid wood passive cabinets—three loudspeakers, including a formidable dual-15" configuration, and an acoustically matched 18" subwoofer that supports pole-mounted or stacked configurations.





LIT000543000

electrovoice.com/livex