



Features

- * Mixer with 6 zone speaker selector for source selection and zone control
- * Build-in mic and recorder for easy voice message recording and storage
- * 3 audio sources direct selection on front panels
- * 6 zone selection buttons on front panel
- * 6 zone paging console work together with the mixer through RJ45 port for remote control and announcement
- * Mic input by XLR type with phantom power and gain control
- st 3 aux inputs for tape, CD and tuner
- st Built-in chime, whose remote trigger and volume is provided
- * 3 voice messages broadcast in continuous and once modes
- $\ensuremath{^*}$ 3 channel pre outputs: music, music/page and page
- st 6 zone line outputs for power amplifier
- * Volume control is provided for mic, music, mater, record and message broadcast, plus bass and treble $\,$ tone control
- * Indications include zone selector, source selector, record state, power and output level
- * 4 levels of priority from high to low: remote paging console, Mic1, chime, pre-recorded message

Specifications

	T /045
Model	T-6245
CONSOLE INPUT	
Sensitivity	\pm 5 mV/600 Ω , \pm 500mV/10K Ω
S/N Ratio	>68dB
Frequency Response	50Hz~17KHz(+1,-3dB)
MIRCOPHONE INPUT	
Sensitivity	\pm 5 mV/600 Ω , \pm 500mV/10K Ω
S/N Ratio	>68dB
Frequency Response	50Hz∼17KHz(-3dB)
Phantom Power	+48V
3 AUXILIARY INPUTS	
Tuner and Tape Input	200mV/47 Ω
Sensitivity/Impedance	
CD Input Sensitivity/Impedance	500mV/47 Ω
S/N Ratio	>90dB
Frequency Response	20Hz~20KHz(+1,-3dB)
CONTROL	
Bass	\pm 12dB at 100Hz
Treble	\pm 12dB at 10KHz
Chime	2 tone active for contact free in priority and BGM
Normal Distortion	>0.05%
OPERATING CONDITION	
Power Supply	~110V/60Hz or ~230V/50Hz & DC 24V
Dimensions	484x303x88mm
Weight	6.58Kg
Max number of paging console	6



Remote paging console input

Remote chime trigger Rear Panel T-6245 Chime volume 48V phantom power for mic Message broadcast volume Message record volume Alarm/Normal status selector Page output Music output Relay music zone COM input-Alarm modes Page/music mix output (once/continuous) selector Zone relay outputs Pre-record message selector (3rd/2nd/1st/off) 400 Mic input Open relay zone contact input Zone 1-6 speaker terminals Tuner input Remote paging console volume Dry contact play message 1 or 2 **CD** input Tape input

Connections

