



## R-4THA/5

Order No.: 0259847

### PRODUCTINFOS

#### **Hand-held UHF PLL transmitter,**

with condenser cartridge.

- Condenser microphone cartridge (cardioid polar pattern)
- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity ( $\pm 15$  dB)
- Lock function/mute function
- 4-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

**There are restrictions or requirements within the EU!**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**

“It also features top-quality workmanship. However, in my opinion, it is visually less appealing than the JSS-4B. Nevertheless, it provides a pleasant sound.”

## FAQ

### **How many wireless systems can be operated simultaneously?**

With optimum local conditions, it is possible to operate 18 wireless systems R-4/5, R-4THA/5, JSS-4B/5, R-4TBM/5 simultaneously.

## TECHNICAL SPECIFICATIONS

### **R-4THA/5**

Description	hand-held microphone
Transmission method	wireless
Polar pattern	cardioid
System	condenser
Carrier frequency range	506-542 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	> 20 h
Audio frequency range	50-18,000 Hz
Max. sound pressure	140 dB
Housing material	
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 50 mm x 253 mm
Weight	260 g