

specifications



White.

Black.



Model	Ci500AW	Ventura 6*	Ventura 5*	Ventura 4*
Design	Two-way Sealed box (ABR)	Two-way Sealed box	Two-way Sealed box	Two-way Sealed box
Drive units	130mm (5.25in.) LF 55 sq.cm ABR 25mm (1in.) HF	160mm (6.5in.) MF/LF 25mm (1in.) HF (Fluid cooled aluminium)	130mm (5.25in.) MF/LF 25mm (1in.) HF (Fluid cooled aluminium)	115mm (4.5in.) LF 19mm (0.75in.) HF (Fluid cooled aluminium)
Frequency response (± 3 dB)	60Hz - 20kHz	54Hz - 20kHz	60Hz - 20kHz	75Hz - 20kHz
Crossover frequency	3kHz	3kHz	3.8kHz	3.5kHz
Amplifier requirements	10 - 70 W	10 - 125 W	10 - 100 W	10 - 80 W
Sensitivity (2.83V/1m)	87dB	90dB	89dB	88dB
Nominal impedance	4 Ω	6 Ω	6 Ω	6 Ω
Finish	White	White	White / Black	White
Net weight	3.8kg (8.36lbs)	3.8kg (8.4lbs)	3.3kg (7.25lbs)	2.4kg (5.3lbs)
Dimensions (H x W x D)	290 x 180 x 173 mm (11.41 x 7.08 x 6.81 in.)	298 x 226 x 183 mm (11.73 x 8.9 x 7.19 in.)	260 x 194 x 165 mm (10.24 x 7.64 x 6.48 in.)	230 x 171 x 154 mm (9.04 x 6.75 x 6.08 in.)

*Independent test laboratory certified IP65