

# RP-400C



## SPECIFICATIONS

<b>FREQUENCY RESPONSE</b>	65Hz - 25kHz
<b>SENSITIVITY</b>	95dB @2.83V / 1m
<b>POWER HANDLING (CONT/PEAK)</b>	75W / 300W
<b>NOMINAL IMPEDANCE</b>	8 Ohm Compatible
<b>CROSSOVER FREQUENCY</b>	1500Hz
<b>HIGH FREQUENCY DRIVER</b>	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
<b>LOW FREQUENCY DRIVER</b>	Dual 4" Cerametallic Cone Woofers
<b>ENCLOSURE MATERIAL</b>	MDF
<b>ENCLOSURE TYPE</b>	Bass Reflex via rear-firing Tractrix® Port
<b>INPUTS</b>	Single Binding Posts
<b>HEIGHT</b>	5.6" (14.24 cm)
<b>WIDTH</b>	16" (40.64 cm)
<b>DEPTH</b>	9.65" (22.86 cm)
<b>WEIGHT</b>	14 lb (6.4 kg)
<b>FINISH</b>	Ebony
<b>ACCESSORIES</b>	Rubber Feet (4)
<b>BUILT FROM</b>	2018

### 90° x 90° SILICON COMPOSITE HYBRID TRACTRIX® HORN

Horn loading maximizes efficiency and increases detail while focusing high frequencies towards the listening area. Proprietary Tractrix® geometry provides the most efficient transfer of high frequency waves into the listening area. The phase plug and compressed molded silicon face ensure smooth frequency response. When combined, the cleanest, most natural sound possible is created.

### LINEAR TRAVEL SUSPENSION (LTS) TITANIUM DIAPHRAGM TWEETER

The exclusive Linear Travel Suspension minimizes distortion for enhanced, detailed performance. LTS tweeters are a hallmark of previous Reference lines, making it a core component of some of the best speakers in the world.

### VENTED TWEETER DESIGN

The new vented tweeter housing reduces standing waves that create unwanted harmonics, resulting in enhanced detail and clarity in high frequency reproduction.

### SPUN COPPER CERAMETALLIC WOOFERS

A signature feature on the Reference Premiere series, Cerametallic™ woofers are exceptionally rigid and lightweight for minimal distortion and maximum efficiency. When paired with the Tractrix horn-loaded LTS tweeter, it provides the highest speaker efficiency in its class.

### TRACTRIX PORTS

Utilizing Tractrix geometry, the Reference Premiere ports allow for the most efficient, fastest air transfer from the cabinet, which reduces port noise for punchier low frequencies. Klipsch Tractrix ports have custom designed inner flares that help reduce air turbulence entering the port. Less turbulent air helps reduce port noise for cleaner, more powerful bass.

### FURNITURE GRADE MATERIALS AND FINISHES

Featuring a scratch resistant Ebony vinyl finish that boasts an elegant satin painted baffle, for a premium look in any listening space.

### STRONG, FLEXIBLE, REMOVABLE GRILLE

Attaches magnetically for an elegant transition from powerful showstopper to discrete performance piece.

### DRAMATIC DETAILS

Copper anodized trim rings, cast aluminum feet, satin painted baffles and a laser etched logo treatment give the Reference Premiere II series a modern, premium look.