General Specifications

Amplifier (Audio) section

Rated Output Power (FTC) (North American) With 8 ohm loads, both channels driven, from 20-20,000 Hz; rated 100 watts per channel minimum RMS power, with no more than 0.08% total harmonic distortion from 250 milliwatts to rated output. Rated Output Power (IEC) (Others) 2 ch \times 160 W at 6 ohms. 1 kHz. 1 ch driven of 1% THD Maximum Effective Output Power (JEITA) (North American) 2 ch \times 170 W at 6 ohms, 1 kHz, 2 ch driven of 10% THD Dynamic Power (*) (*)IEC60268-Short-term maximum output power 240 W (3 Ω, Front) 210 W (4 Ω. Front) 120 W (8 Ω, Front) THD+N (Total Harmonic Distortion+Noise) 0.08% (20 Hz - 20.000 Hz, half power) Input Sensitivity and Impedance (1 kHz, 100 W/8 Ω) 200 mV/47 kΩ (LINE (Unbalance)) 3.5 mV/47 kΩ (PHONO MM) Rated RCA Output Level and Impedance 1 V/470 Ω (SUBWOOFER PRE OUT) 200 mV/2.3 kΩ (ZONE LINE OUT) Phono Overload 70 mV (MM 1 kHz, 0.5%) Frequency Response 10 Hz - 100 kHz/+1 dB, -3 dB (Direct/Pure Audio) **Tone Control Characteristics** ±10 dB, 90 Hz (BASS) ±10 dB, 7.5 kHz (TREBLE) Signal to Noise Ratio 106 dB (IHF-A, LINE IN, SP OUT) 80 dB (IHF-A, PHONO IN, SP OUT) Speaker Impedance 4 Ω - 16 Ω Headphone Output Impedance 330 Ω Headphone Rated Output 80 mW (32 Ω, 1 kHz, 10% THD)

Tuner Section

FM Tuning Frequency Range 87.5 MHz - 107.9 MHz (North American) 87.5 MHz - 108.0 MHz, RDS (Others) AM Tuning Frequency Range (North American) 530 kHz - 1710 kHz DAB Tuning Frequency Range (Others) 174.928 MHz - 239.200 MHz Preset Channel 40

Network Section

Ethernet LAN 10BASE-T/100BASE-TX Wireless LAN IEEE 802.11 a/b/g/n standard (Wi-Fi[®] standard) 5 GHz/2.4 GHz band

BLUETOOTH Section

Communication system **BLUETOOTH Specification version 4.1+LE** Frequency band 2.4 GHz band Modulation method FHSS (Frequency Hopping Spread Spectrum) Compatible BLUETOOTH profiles A2DP 1.2 AVRCP 1.3 HOGP-Host (Client) HOGP-HID Device (Server) HID Service (HIDS) Supported Codecs SBC AAC Transmission range (A2DP) 20 Hz - 20 kHz (Sampling frequency 44.1 kHz) Maximum communication range Line of sight approx. 48 ft. (15 m) (*)

(*)The actual range will vary depending on factors such as obstacles between devices, magnetic fields around a microwave oven, static electricity, cordless phone, reception sensitivity, antenna's performance, operating system, software application, etc.

General

Power Supply AC 120 V, 60 Hz (North American) AC 230 V, 50 Hz (Others) Power Consumption 260 W 0.1 W (Stand-by, North American) 0.15 W (Stand-by, Others) 35 W (No-sound) 4.2 W (HDMI Standby Through, North American) 4.5 W (HDMI Standby Through, Others) 2.6 W (Network Standby, North American) 2.8 W (Network Standby, Others) Dimensions (W \times H \times D) 17-1/8" × 5-7/8" × 12-15/16" 435 mm × 149.5 mm × 329 mm Weight 18.1 lbs/8.2 kg (North American) 8.7 kg/19.2 lbs (Others)

HDMI

Input IN1 (BD/DVD), IN2 (CBL/SAT), IN3 (PC), IN4 (GAME) Output OUT Supported Deep Color, x.v.ColorTM, LipSync, Audio Return Channel, 3D, 4K 60Hz, CEC, Extended Colorimetry (sYCC601, Adobe RGB, Adobe YCC601), Content Type, HDR Audio Format DSD, PCM Maximum Video Resolution 4k 60 Hz (YCbCr 4:4:4)

Compatible input resolutions

HDMI input

4K, 1080p/24, 1080p, 1080i, 720p, 480p/576p Composite input 480i/576i

The output from the HDMI OUT jack to the TV is the same resolution as the input.

Audio Inputs

Digital OPTICAL IN1 (GAME), IN2 (TV/TAPE) COAXIAL IN (CD) Analog IN1 (PC), IN2 (TV/TAPE), IN3 (CD), PHONO

Audio Outputs

Analog ZONE2 LINE OUT 2 SUBWOOFER PRE OUT Speaker Outputs SPEAKERS A: FRONT L/R SPEAKERS B: FRONT L/R (North American models are banana plug ready) Phones PHONES (Front, Ø1/4″/6.3 mm)

Others

USB: 2 (Front: Ver.2.0, 5 V/1 A, Rear: Ver.2.0, 5 V/ 500 mA) Ethernet: 1 RI REMOTE CONTROL: 1 IR IN: 1 IR OUT: 1

Power consumption in standby mode

- In the following cases, the power consumption in standby mode may reach up to a maximum of 15 W:
- When "Network Standby" is set to "On"
- When "HDMI CEC" is set to "On"

- When "HDMI Standby Through" is set to other than "Off"
- When "Bluetooth Wakeup" is set to "On"
- When "USB Power Out at Standby" is set to "On"