

Loudspeakers

Up 40

Full-range, open-backed, 4" ceiling speaker



Optimal Audio



FEATURES

- 4" Full Range Driver
- Discreet size without back can
- Unobtrusive Design
- 70/100V line operation
- Range of power taps
- Wide Conical Coverage Pattern
- Integrated Mounting Hardware

Up 40 is a discreet 4" ceiling speaker delivering consistent coverage and crisp, clear sound to a wide range of cost conscious, commercial environments — from hotels and concourses to retail outlets, bars and restaurants.

Up 40 is supplied without a back can for ceilings with a minimum cavity depth, while an integral fixing system is included to achieve a simple and clean installation. The steel perforated grille is finished in neutral white.

Up 40 features a 4" (105mm) driver which is ideal for both music and

speech reproduction. A 130° conical coverage pattern ensures the system is delivering sound where it needs to go.

Each Up 40 has been specifically designed to run on 70 or 100 volt line systems.

SmartAmps or Zone will provide optimal performance and loudspeaker protection. When coupled with the Zone series, a ZonePad and the WebApp makes setting up a system and end user control simple and intuitive.

APPLICATIONS



Cafes



Bars/
Restaurants



Retail



Wedding
Venues



Hotels



Education
Facilities



Houses of
Worship



Corporate
Offices




Museums



Fitness Studios



Residential







Loudspeakers

Up 40

Full-range, open-backed, 4" ceiling speaker



Optimal Audio



SPECIFICATIONS

TYPE	: Full range, passive, ceiling speaker
FREQUENCY RESPONSE (with preset)	: 87Hz - 15kHz ± 3dB
DRIVERS	: 4" (105mm), Coated paper
RATED POWER (AES)	: 10W
NOMINAL IMPEDANCE	: 70/100V
SENSITIVITY (1W/1m)	: 93dB
MAXIMUM SPL	: 100dB (cont)
RECOMMENDED HIGH-PASS FILTER	: 24dB/Octave @ 80Hz
TRANSFORMER TAPS @ 70V	: 6, 3, 1.5, 0.75 Watt
TRANSFORMER TAPS @ 100V	: 6, 3, 1.5 Watt
DISPERSION (-6dB)	: 130° conical
BAFFLE	: ABS
PROTECTIVE GRILLE	: Perforated steel
CONNECTORS	: Bare wires
FITTINGS	: C-ring support backing plate
DIMENSIONS	: (W) 202mm x (H) 138.2mm x (D) 202mm (W) 7.95" x (H) 5.44" x (D) 7.95"
WEIGHT	: 1.3kg (2.9lbs)
INCLUDED ACCESSORIES	: 2 tile support rails (for 2 ft or 600 mm tile spans), cutout template, paint shield, removable locking multi-pin connector
RECOMMENDED SUB	: Sub 10



Paint Finish



Weight

optimal-audio.co.uk

© 2021. Optimal Audio Group Ltd.