MADRID TMS152

2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications

- 2 way full range loudspeaker for portable PA and installation applications
- 800 Watts continuous,3,200 Watts peak power
- Ideal for FOH, side and drum fill applications
- Carbon fibre loaded
 15" low frequency driver with inside/outside wound coil
- Titanium dome 1.4" neodymium motor compression driver
- Switchable passive/bi-amp operation for flexibility of use
- Low distortion waveguide provides
 75° H x 50° V dispersion
- 15 mm (%") birch plywood enclosure with hard wearing semi matt black paint finish
- Rugged powder coated perforated steel mesh grille
- Dual angle pole mount for accurate audience coverage
- Durable handles for easy lifting and carrying
- Multiple internal rigging points for installation applications
- Neutrik speakON* NL4 connectors for reliable long life operation
- 3-Year Warranty Program*
- Designed and engineered in England



The 2 way full range TMS152 is a switchable passive/bi-amp 15" 3,200 Watt loudspeaker system designed for a wide range of portable speech and music sound reinforcement applications. The TMS152 is designed to work in conjunction with **TURBOSOUND** loudspeaker management systems, providing optimal performance



for FOH, side and drum fill applications, as well as offering considerable flexibility to readily adapt to varying venue requirements.

The TMS152 loudspeaker features a carbon fibre loaded 15" low frequency driver with an inside/outside wound low mass voice coil for improved transient response, and a titanium dome 1.4" neodymium motor compression driver mounted on a 75° horizontal by 50° vertical low distortion waveguide. All drivers are matched with an internal passive crossover network in a reflex-loaded enclosure, and bi-amp mode can be enabled by means of a rear panel switch.

Finished in a highly durable semi matt black paint, the cabinet is constructed from 15 mm (%") birch plywood, and includes a rugged powder coated perforated steel mesh grille backed with reticulated foam. The TMS152 includes internal M10 threaded rigging points for permanent installation, a dual-angle pole mount socket for high or low height use with 35 mm poles/ speaker stands to optimise audience coverage, and durable handles for easy transport. A rear panel connector plate carries two Neutrik speakON* NL4 connectors for input and link connections to additional enclosures.





MADRID TMS152

2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications



You Are Covered

We always strive to provide the best possible Customer Experience. Our products are made in our own MUSIC Group factory using state-of-the-art automation, enhanced production workflows and quality assurance labs with the most sophisticated test equipment available in the world.


As a result, we have one of the lowest product failure rates in the industry, and we confidently back it up with a generous 3-Year Warranty program.




MADRID TMS152

2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications

Frequency Response Sensitivity 1 W / 1 m



Impedance







MADRID TMS152

2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications

Horizontal Beamwidth



Vertical Beamwidth








MADRID TMS152


2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications


Horizontal Polar Plots
















MADRID TMS152


2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications


Vertical Polar Plots
















MADRID TMS152


2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications

Dimensions









MADRID TMS152

2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications

Technical Specifications

System	
Frequency Response	55 Hz — 20 kHz ±3 dB
	45 Hz — 20 kHz -10 dB
Nominal Dispersion	75° H X 50° V @ -6 dB Points
Directivity Factor (Q)	12.8
Directivity Index (DI)	11.1
Power Handling (IEC)	
Passive	800 W continuous, 3,200 W peak
Bi-amp	LF: 800 W continuous, 3,200 W peak
· 	HF: 75 W continuous, 300 W peak
Sensitivity	97 dB (1 W @ 1 m)
Maximum SPL	
Passive	126 dB continuous, 132 dB peak
Bi-Amp	LF: 126 dB continuous, 132 dB peak
	HF: 128 dB continuous, 134 dB peak
Impedance	
Passive	8 Ω
Bi-Amp	LF: 8 Ω
	HF: 6 Ω
Crossover Type	Passive / bi-amp, switchable
Components	1 x 15" (394 mm) LF driver
	1 x 1.4" (36 mm) HF compression driver

Enclosure	
Connectors	2 x Neutrik speakON* NL4
Wiring	
Passive	Pins 1+ / 1- input, pins 2+ / 2- link
Bi-Amp	Pins 1+ / 1- LF, pins 2+ / 2- HF
Dimensions HWD	716 x 432 x 406 mm (28.2 x 17.0 x 16.0")
Net Weight	27.7 kg (61.0 lbs)
Construction	15 mm (%") birch plywood
Finish	Semi matt black paint
Grille	Powder-coated perforated steel
Flying Hardware	M12 x 12 points



MADRID TMS152

2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications







MADRID TMS152

2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications







MADRID TMS152

2 Way 15" Full Range Loudspeaker for Portable PA and Installation Applications





For service, support or more information contact the TURBOSOUND location nearest you

Europe MUSIC Group Services UK Tel: +44 156 273 2290 Email: CARE@music-group.com

USA/Canada MUSIC Group Services NV Inc. Tel: +1702 800 8290 Email: CARE@music-group.com Japan MUSIC Group Services JP K.K. Tel: +81 3 6231 0454 Email: CARE@music-group.com

