

GIYA G 1 SPIRIT

The driving force behind Vivid Audio is the continuous quest for perfection.

Welcome to the Vivid Audio GIYA G1 Spirit.

3

Y

GIYA G1 SPIRIT

WELCOME TO THE CONTINUOUS QUEST FOR PERFECTION

It has been said that improving the G1 would be like gilding a lily, there's no question that the bar has been set very high. Nevertheless, the driving spirit behind Vivid Audio is that if there is any hint that an improvement is possible, it will be pursued, tested, perfected and implemented.

When reviewing improvements it resulted in the opportunity to reconsider multiple aspects of the design. Including a new aspect to the exterior shell with longer wider port for increased linear LF output, new C225-100 bass drivers, Lower-mid driver C125-75 with carbon rings, new chassis and CNC machined sandwich composite stiffening braces.

Specification

Configuration	4-way, 5 driver
Cabinet material	Glass reinforced balsa cored sandwich composite
Cabinet colour	Piano Black, Pearl White, Oyster Matte
Bespoke cabinet colour	Bespoke colour options available on request
Drive units	HF: D26 – 26 mm metal dome unit with Tapered Tube loading
	Mid: D50 – 50 mm metal dome unit with Tapered Tube loading
	Lower-mid: C125-75s – 125 mm alloy/carbon diaphragm with 75 mm voice coil
	Bass: 2 x C225-100, 225 mm alloy diaphragm with 100 mm voice coil in 45 mm gap
Bass loading	Exponentially tapered tube enhanced bass reflex
Sensitivity	92 dB @ 2,83 VRMS at 1 m on axis
Nominal impedance (Ω)	6 nominal, 3 minimum at 20 KHz no phase shift at Zmin
Frequency range (Hz)	-6 dB points: 25 – 36.000
First D26 Break Up mode (Hz)	44.000
Frequency response (Hz)	29 - 33.000 +/- 2 dB on reference
Harmonic distortion	< 0,3% over frequency range
(2nd and 3rd harmonics)	
Cross over frequencies (Hz)	220 - 880 - 3.500
Power handling (music program)	1.600 watts rms
Loudspeaker dimensions	1.600 mm (H) x 440 mm (W) x 820 mm (D)
Net weight	67,4 kg (internal crossover) 62 kg (external crossover)



For more details about the GIYA G1s or accessories to compliment, please consult your local specialist retailer, or visit www.vividaudio.com









Headquarters

Vivid Audio Holding B.V. • Kaap Hoorndreef 66 • 3563 AW Utrecht • The Netherlands Tel: +31 (0) 626 776 787 • Email: info@vividaudio.com

vividaudio.com