

Portable Projector Vivitek DX561

Versatile and portable XGA projector



Features

- 4,000 ANSI lumens of brightness and 15,000:1 contrast ratio for clear, crisp and bright presentations
- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- XGA (1024 x 768) native resolution scalable up to a maximum UXGA (1600 x 1200) resolution
- Innovative 5 segment colorwheel (RGBYW) provides improved brightness and automatic gain control
- Convenient top loading design for easy lamp replacement
- Multiple inputs for easy connection to a variety of devices: HDMI/MHL v1.4, VGA-In (x2), S-Video, composite video
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Source filtering function to save time locating device signal source
- 3D ready with 3D-Ready via DLP® Link™
- Audio ready with built-in 2 watt audio speaker, audio-in and audio out ports
- Reduces energy consumption to less than 0.5W in standby mode
- Keypad lock prevents accidental system adjustments
- 2.3kg/5lbs for easy portability

Photos

Display Type Single 0.55" DLP® Technology by TI Brightness 4,000 ANSI Lumens Native Resolution XGA (1024 x 768) WUXGA (1920x1200)@60Hz Maximum Resolution Contrast Ratio 15.000:1 3,500/5,000/7,000 Hours (Normal/Eco. Lamp Life/Type Mode/Dynamic Eco. Mode), 240W/190W Throw Ratio 1.92 - 2.14:1 Image Size (Diagonal) 23" - 256" 1 - 10m (3.287ft to 32.8ft) **Projection Distance Projection Lens** F = 2.52 - 2.73, f = 21.8 - 24mm Zoom Ratio 1.1x Aspect Ratio 4:3 Native Offset 114% ±10% Vertical +/-40 Keystone Correction 15, 31 - 91.4kHz Horizontal Frequency Vertical Frequency 24 - 30Hz, 47 - 120Hz Yes (Supports DLP[®] Link™) **3D** Functionality 2W (Mono) Speakers VGA, SVGA, XGA, SXGA, SXGA+, UXGA, Computer Compatibility WUXGA@60hz, Mac SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, Video Compatibility 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L) HDMI/MHL v1.4, VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), I/O Connection Ports VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Kensington® Security Slot, Keypad Lock Security Solutions (Power Only) Dimensions (W x D x H) 274.6 x 212 x 100mm (10.8" x 8.3" x 3.9") 2.3kg (5lbs) Weight Available Color Two-Tone: White/Gray 38dB/34dB (Normal/Eco Mode) Noise Level Power Supply AC 100-240V, 50/60Hz 240W (Eco. Mode), 310W (Normal Mode), **Power Consumption** <0.5W (Standby) AC Power Cord, VGA Cable, Remote Standard Accessories Control w/Batteries, Documentation Kit Replacement Lamp, RS-232 Cable, Lens **Optional Accessories** Cap, Carry Case, Filter (China only)

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.



Specifications









V4 - 12312015

