

APPENDIX

Specifications

The specifications of this product are as follows.

■ Sound bar

Amplifier section

Maximum rated output power

- Front L/R 20 W × 2 channels

Speaker section

Front L/R

- Type Acoustic suspension type
(non-magnetic shielding)
- Driver 4.6 cm (1-13/16") cone × 2
- Frequency response 210 Hz to 22 kHz
- Impedance 6 Ω

Decoder

Supported audio signal
(HDMI (ARC)/optical input)

PCM (up to 2 channels)
Dolby Digital (up to 5.1 channels)

Input jacks

Digital optical 2 (TV, OPTICAL)

Analog (3.5 mm stereo mini) 1 (ANALOG)

Output jacks

HDMI 1 (HDMI OUT/TV (ARC))

Other jacks

USB 1 (UPDATE ONLY)

Bluetooth

Function	Sink function (source device to this unit)
Bluetooth version	Ver 5.0
Supported profiles	A2DP
Supported codecs	Sink function: SBC, AAC
Bluetooth class	Bluetooth Class 1
Range (line-of-sight)	Approx. 10 m (33 ft)
Supported content protection method	SCMS-T (sink function)
Models for U.K. and Europe	
<ul style="list-style-type: none"> Radio frequency 	2402 MHz to 2480 MHz
<ul style="list-style-type: none"> Maximum output power (EIRP) 	7.8 dBm (6.0 mW)

General

Power supply	
<ul style="list-style-type: none"> Models for U.S.A., Canada, Taiwan and Mexico 	AC 100 to 120 V, 50/60 Hz
<ul style="list-style-type: none"> Models for U.K., Europe, and other areas 	AC 100 to 240 V, 50/60 Hz
Power consumption (AC adaptor output voltage/current)	20 V/2.1 A
Standby power consumption	
<ul style="list-style-type: none"> [Models for U.S.A., Canada, Taiwan and Mexico] <ul style="list-style-type: none"> HDMI Control/Bluetooth Standby: Off HDMI Control/Bluetooth Standby: On [Models for U.K., Europe, and other areas] <ul style="list-style-type: none"> HDMI Control/Bluetooth Standby: Off HDMI Control/Bluetooth Standby: On 	0.3 W 0.5 W 0.3 W 0.5 W
Dimensions (W x H x D)	
<ul style="list-style-type: none"> Installing the Sound Bar in front of a TV, etc. 	600 × 64 × 94 mm (23-5/8" × 2-1/2" × 3-3/4")
<ul style="list-style-type: none"> Mounting the Sound Bar on a wall, with spacers 	600 × 64 × 102 mm (23-5/8" × 2-1/2" × 4")
Weight	1.3 kg (2.9 lb)

NOTE

The contents of this User Guide apply to the latest specifications as of the publishing date. The latest version of the User Guide is available to download from the Yamaha website.

■ Subwoofer

Amplifier section

Maximum rated output power	50 W
----------------------------	------

Speaker section

• Type	Bass reflex (non-magnetic shielding)
• Driver	13 cm (5-1/8") cone × 1
• Frequency response	40 Hz to 210 Hz
• Impedance	3 Ω

Wireless function (Wireless communication between the sound bar and subwoofer)

• Radio frequency band	2.4 GHz
• Transmission range	Approx. 10 m ([33 ft] without interference)

Models for U.K. and Europe

• Radio frequency	2405.35 MHz to 2477.35 MHz
• Maximum output power (EIRP)	9.0 dBm (7.9 mW)

General

Power supply

• Models for U.S.A., Canada, Taiwan and Mexico	AC 100 to 120 V, 50/60 Hz
• Models for U.K., Europe, and other areas	AC 100 to 240 V, 50/60 Hz

Power consumption	20 W (Rated)
-------------------	--------------

Standby power consumption	0.8 W
---------------------------	-------

Dimensions (W x H x D)

• Installing the subwoofer upright, with non-skid pads	160 × 337 × 364 mm (6-1/4" × 13-1/4" × 14-3/8")
• Installing the subwoofer horizontal, with non-skid pads	335 × 162 × 364 mm (13-1/4" × 6-3/8" × 14-3/8")

Weight	5.7 kg (12.6 lb)
--------	------------------

NOTE

The contents of this User Guide apply to the latest specifications as of the publishing date. The latest version of the User Guide is available to download from the Yamaha website.