



4 mic



Bluetooth



Audio Link



Clean Channel



Battery Meter



EJ-7XT+
Bodypack Transmitter



EJ-7T+
Bodypack Transmitter



EJ-701TM+
Handheld microphone

EJ-701TS+
Handheld microphone



HDC-702
Charger



HDC-707
Charger

- ✓ 120W power output (max).
- ✓ Two-way speaker – 8” woofer and 1” tweeter – deliver great sound projection.
- ✓ Supports max two ACS receiver modules (DR-501A) or Duo receiver modules (DR-500) allows 4 wireless microphones to operate concurrently.
- ✓ Duo-receiver provides SCAN function for a clear channel to use, and SYNC to target microphones at same channel as receiver.
- ✓ Integrated Bluetooth function for audio streaming from smartphone and tablet.
- ✓ Built-in Echo sound effect & delay applied on wireless mics and audio inputs (GPA-828 only).
- ✓ Various audio player modules for option – MP3, CD, DVD, pitch control or recording – at users’ choice.
- ✓ Voice priority allows a reduced music volume when a microphone is used.
- ✓ 4-segment battery meter for charging and power status reading.
- ✓ Two power models – AC or Battery powered.
- ✓ Runs 4-6 hours on a charge (built-in battery charger).
- ✓ Retractable handle and wheels allow users to move without difficulty.

Portable PA

| | |
|------------------------|---|
| Output power | 120W (max.) / 80W (RMS) |
| Speaker | 8" woofer and 1" tweeter |
| Receiver modules | DR-501A or DR-500, up to 2 |
| Audio inputs | Combo/6.3Φ-Mic in, 3.5Φ- Aux in, RCA-Line in, MIC/LINE Switch |
| Bluetooth Receiver | Built-in |
| Effects | ECHO / DELAY (GPA-828 only) |
| Audio outputs | 3.5Φ- Aux OUT, RCA-Line out |
| Power requirements | 100~240 VAC switching power supply |
| Battery | 12V, 4.5 Ah x 2 (Lead-Acid) rechargeable batteries |
| Battery indicator | 4 LEDs to indicate battery autonomy status |
| Operating life | 4 ~ 6 hours |
| Charging time | 6 ~ 8 hours |
| Dimensions (D x W x H) | 264 x 301 x 511 (mm) |
| Weight | Approx. 16kg (35 lbs), batteries included |

Wireless System

| | |
|-------------------------|--|
| Oscillation type | PLL synthesized control OSC |
| Carrier frequency range | 514 ~ 865 MHz (country dependent) |
| Receiver mode | Scan, Sync, manual |
| Adjustable channels | 16 or 96 preset channels, by frequency range |
| Display status | Channel number, signal strength |
| Switching bandwidth | Max. 12 MHz |
| Ambient temperature | -10 °C ~ 50 °C |
| Maximum deviation | 80 kHz, with level limiting |
| Squelch | Tone key and noise lock dual-squelch |
| Frequency response | 70 Hz ~ 17 kHz |
| Operating range | 50 ~70 M (open field) |

·Specifications are subject to change.



OKAYO ELECTRONICS CO., LTD.

No.2, Gongye 10th Rd., Dali Dist., Taichung 41280, Taiwan

☎ (886) 4 2491 4666

✉ okayo@okayo.com

☎ (886) 4 2491 4755

🌐 www.okayo.com